## Cleaning method, cleaning apparatus and electro optical device

Publication number: TW278536B

Publication date:

2007-04-11

Inventor:

HOSODA TOSHIKO (JP); YOTSUYA SHINICHI (JP)

Applicant:

SEIKO EPSON CORP (JP)

Classification:

- international: B08B3/08; C23F4/00; B08B3/00; B08B3/12;

C23C14/00; C23C14/04; C23C14/24; H01L21/302; H01L21/44; H01L21/461; H01L51/50; H05B33/10; H05B33/14; B08B3/08; C23F4/00; B08B3/00; B08B3/12; C23C14/00; C23C14/04; C23C14/24; H01L21/02; H01L51/50; H05B33/10; H05B33/14;

- European:

B08B3/12

Application number: TW20040135877 20041122 Priority number(s): JP20030403071 20031202

Also published as:

US2005115594 (A JP2005161190 (A) CN1623688 (A)

Report a data error he

## Abstract of TW278536B

To provide a washing method and a washing apparatus capable of easily removing organic matter adhering to an evaporation mask of a low-molecular organic EL apparatus. The washing apparatus is an apparatus 1 for washing organic matter adhering to the evaporation mask of the low-molecular organic E apparatus and comprises a first stage 10 for treating the evaporation mask 140 with a pyrrolidone derivative; a second stage 20 for rinsing the evaporation mask 140 with water; a third stage 30 for rinsing the evaporation mask 140 with flowing water; a fourth stage 40 for treating the evaporation mask 140 with ethanol; a fifth stage 50 for drying the evaporation mask 140; and transportation means 5 for successive transporting the evaporation mask 140 to the respective stages. It is preferable to use N-methyl-2-pyrrolidone as the pyrrolidone derivative.

Data supplied from the esp@cenet database - Worldwide